



TRAILER

SPECIFICATIONS

Length	13.6 m	44' 7"	
Width	2.5 m	8' 2"	
Height	4.12 m	13' 6"	
Cargo Space	11.4 x 1.5 x 1.5 m	37' 5" x 5' x 5'	
Weight	26000 kg	57300 lbs	

STAGE FLOOR

Length and Depth	13.1 x 11.58 m	43' x 38"
Length and Depth with Extension Platforms	22.9 x 14.02 m	75' x 46'
Height from Ground	1.83 m	6'
Design Live Load	490 kg/m²	100 lbs/ft ²
Type of Surface	Plywood on steel	

ROOF

Length and Depth	13.6 x 11.63 m	44' 7" x 38' 2"
Clearance	7.77 to 8.93 m	25' 6" to 29' 3"
Overall Height with Banner	12.16 m	39' 9"
Type of Surface	Fibreglass bonded on steel	
Load Bearing Capacity †	10890 kg	24000 lbs
6 Trusses (T1s, T2s and T3s)	2000 kg each	4400 lbs each
4 Movable Rigging Beams	1000 kg each	2200 lbs each
2 Front Overhang Points	454 kg each at 0.70 m	1000 lbs each at 2' 3"
2 Cantilevered Side Trusses	2995 kg each at 3.43 m	6600 lbs each at 11' 3"
2 Line Array Rigging Beams *	1814 kg each at 0.76 or 1.52 m	4000 lbs each at 2' 6" or 5'

PRACTICAL ASPECTS

Installation Time once Levelling Complete	4 to 5 Hours - Less without windwalls
Personnel Required	2 Certified technicians and 3 stage hands
Site Preparation	None
Heavy Machinery Required	None
Mode of Transportation	1 Fifth-wheel tractor
Gust Wind Resistance	97 km/h (60 mph) with windwalls or 145 km/h (90 mph) without windwalls
Promotional Visibility	Rolling billboard or banners and posters
Windwalls *	Weatherproof, fire-retardant reinforced vinyl
Vertical Banner Supports *	Side truss extensions - More than 365 m ² (1200 sq. ft) of promotional space
Horizontal Banner Supports *	For more than 10.2 m ² (110 sq. ft) of promotional space
Floor Extension Platforms *	Integrated brackets - easy to install

Values indicated are nominal. Due to STAGELINE'S product improvement policy, technical specifications may change without notice.

Offered in option.



[†] Please refer to rigging plan.